

TOLUENE

PROPERTY	SPECIFICATION VALUE	TEST METHOD
PURITY WT%	99.9 MIN (EXPECTED VALUE:99.98)	ASTM D 2360-00
NON AROMATICS WT%	0.1 MAX	ASTM D 2360-00
BENZENE WT%	0.03 MAX	ASTM D 2360-00
DISTILLATION RANGE °C AT 760MM HG	1.0 MAX INCLUDING 110.6	ASTM D 850-00
APPREANCE	CLEAR LIQUID FREE OF SEDIMENTATION OR HAZE AT 18.3 TO 25.6°C	VISUAL
TOTAL SULFUR WT. PPM	1.0 MAX	ASTM D 4045-99
COPPER CORROSION	PASS (1A TO 1B)	ASTM D 849-97
COLOR, PT-CO SCALE	20 MAX (EXPECTED VALUE:10)	ASTM D 1209-00
ACID WASH COLOR	2 MAX	ASTM D 848-97
ACIDITY	NONE DETECTED	ASTM D 847-96
SPECIFIC GRAVITY AT 15.56/15.56°C	0.869-0.873	ASTM D 4052-96
S2O/H2S	NONE DETECTED	ASTM D 853-97
VAPOR PRESSURE PSI	1.1	ASTM D 323-99A